

Incremental Magnetic Sensing Head IKS9.3-Z1.50P2V5D1R1F1000T2L2C4E1



Width: 13 mm (metal case)
Reference Signal: 1.50
Pole Pitch: 2 mm
Supply Voltage: 5 V
Interface: RS422
Resolution: 1 μ m
Output Frequency: 1000 kHz
Cable Type: Drag chain quality (\varnothing 4 mm)
Cable Length: 2 m
Connector: D-SUB 15 (male)
LED Mode: Remote support avail.
Hysteresis: 1.95
Error Behaviour: Standard

Technical characteristics

- Incremental magnetic sensor
- Pole pitch 2 mm
- For linear and rotary scales

Benefits

- Non-contact, quick position measurement
- Precise
- Programmable
- No wear from usage
- Resistant to dust, cooling lubricant emulsion, oil, etc.
- Unlimited measuring length

Electrical and mechanical parameter

Pole pitch	
Signal period	
Resolution	
Repeatability	
Voltageg	
Current consumption	65 mA \pm 5 % (UB = 5 V)
Zulässige Last	
Protection class	IP67 (EN 60529)
Operating temperature	- 20°C. + 70°C
Humidt	
Maximum speed	
Interface	
Cable length	2 m
Connector	

Output signals

Output circuit	
Clock frequency	
Tc	
Signal	A, /A, B, /B, Z , /Z
Signal amplitude	5V
Reference voltage U ₀	
Phase shift A and B	90° ± 10° electrical
Maximum frequency (at 2 m/s)	

V+	
V-	
A	
/A	
B	
/B	
CK	
/CK	
D	
/D	
SCH	

Dimensions

Magnetics that count



© BOGEN Electronic GmbH

17.08.2019 17:56

<https://www.bogen-electronic.com/en/magnetic-measurement-solutions/sensing-heads/incremental/linear/00052913.html>

All statements without guarantee. Data can be change at any time.